

- Dual channel for stereo applications
- Balanced inputs and outputs
- Connects in-line for easy test signal insertion
- Quick identification of insertion point with voice ID
- Short Duration Audio Test Sequence for rapid automatic checkout of audio lines
- Single button selection of line-up tone
- Manual mode allows selection of frequency and amplitude

The ASG 100 Audio Signal Generator supplies test tone sequences used to perform automated measurements with the VM 700A Option 40 Audio Measurement Set. In approximately 30 seconds, these two products can totally characterize the audio performance of studios, STLs, transmitters and satellite uplinks. Its small size and quick line-up tone selection make it well suited for verifying microwave links from EFP/ENG vans.

The ASG 100 provides tone sequences for testing to ANSI T1.502-1988, EIA/TIA-250-C or CCITT 0.33 standards. Each sequence begins with a one second FSK signal unique to that sequence. The FSK contains a programmable four digit ID, indicating the source of the test signals. It also communicates to the VM 700A Option 40 the appropriate stored measurement program to use and marks the beginning of the test tones. The remainder of the sequence consists of a number of test tones at defined levels and frequencies. Each tone is typically one second in duration.

Audio measurement results obtained via automatic monitoring can be included in the VM 700A's Auto mode

ASG 100 AUDIO SIGNAL GENERATOR ^{\$1800}



ASG 100 Audio Signal Generator.

video measurements display, along with the time, date and four digit ID of the last sequence received. The VM 700A Option 40 provides timed reports and logging of measurement results falling outside user defined limits.

Installing the ASG 100 in-line near the program source eliminates the need to change cables every time you perform a test. A fail-safe feature prevents interruption of audio service due to loss of power or instrument malfunction. The tone sequence can be initiated by front panel controls or rear panel contact closure. After insertion of a tone sequence is completed, the ASG 100 returns to a bypass mode. The ASG 100 also has the capability to store four seconds of voice in non-volatile memory with convenient front panel microphone and controls. To alert personnel that a test tone

sequence is about to be inserted, the stored voice message may be inserted prior to the sequence. To aid in remote setups, the ASG 100 can "loop" on the stored message. Selecting the Line-Up function on the ASG 100 automatically brings up a user defined signal for setting operating levels of the audio source point. The Silence function is useful for facilitating system noise measurements or quickly removing any signal that is over-driving the audio line. The Manual mode provides a means of setting the output frequency or amplitude to any value within the instrument's range. In this mode of operation the ASG 100 acts like a conventional audio tone generator.

Tektronix
COMMITTED TO EXCELLENCE

Measurement Sequence for Stereophonic Pairs, CCITT Recommendation 0.33

Time Interval	Channel A Sending unit		Channel B Sending unit		Program number: 01
Seconds	Frequency (Hz)	Level (dBm0)	Frequency (Hz)	Level (dBm0)	Measuring function
1	1650/1850	-12	—	—	Start/source/program identification
1	1,020	0	1,020	0	Received level
1	1,020	-12	1,020	-12	Frequency response interchannel Gain and phase
1	40	-12	40	-12	
1	80	-12	80	-12	
1	200	-12	200	-12	
1	500	-12	500	-12	
1	820	-12	820	-12	
1	2,000	-12	2,000	-12	
1	3,000	-12	3,000	-12	
1	5,000	-12	5,000	-12	
1	6,300	-12	6,300	-12	
1	9,500	-12	9,500	-12	
1	11,500	-12	11,500	-12	
1	13,500	-12	13,500	-12	
1	15,000	-12	15,000	-12	
1	1,020	+9	1,020	+9	
1 ^{a)}	—	—	—	—	
1	60	+9	60	+9	Crosstalk and circuit transposition
1	2,040	-12	—	—	
1	—	—	2,040	-12	Compandor test
1	800	+6	800	+6	
1	800	-6	800	-6	
1	800	+6	800	+6	Signal-to-noise ratio
8	—	—	—	—	

^{a)} Waiting interval.

SPECIFICATIONS

Frequency Related

Range
10 Hz to 20 kHz

Resolution
1 Hz

Accuracy
±0.1%

Amplitude Related

Range
-90 dBu to +24 dBu
(24 μ V to 12.3 V)

Resolution
0.1 dB

Accuracy
±0.2 dB at 1 kHz

Flatness
±0.2 dB 20 Hz to 20 kHz

Distortion

THD+N
<0.01% (<0.005% at full output)
20 Hz to 20 kHz measured over
an 80 kHz bandwidth

Other

Signal-to-Noise Ratio
>80 dB at 0 dBu output level

Input Connectors
Two XLR; balanced; looped
through to output unless
generator is in INSERT mode

Output Connectors
Two XLR, balanced

Output Impedance
10 ohms, 600 ohms, or user
defined; balanced

Level Difference Between
Channels
≤0.2 dB

Phase Difference Between
Channels
≤1 degree, 10 Hz to 20 kHz

Power Source

Voltage Range
90 to 260 Vac

Power Consumption
20 W typical

Physical Characteristics

Dimensions
Width—8.1 in. (206 mm)
Height—1.7 in. (43 mm)
Length—18.0 in. (458 mm)

Net Weight
3.25 lbs (1.48 kg)

Environmental

Temperature
Operating
0°C to +50°C
Non-operating
-40°C to +65°C

ORDERING INFORMATION

**ASG 100 Audio Signal
Generator**

For further information, contact:

**U.S.A., Asia, Australia, Central & South
America, Japan**
Tektronix, Inc.
Television Division, MS 58-699
P.O. Box 500
Beaverton, Oregon 97077
Phone: (503) 627-1843
TLX: 151754
FAX: (503) 627-4486

**Tektronix sales and service offices around
the world:**
Algeria, Argentina, Australia, Austria, Bahrain,
Bangladesh, Belgium, Bolivia, Brazil, Bulgaria,
Canada, Chile, Peoples Republic of China, Colombia,
Costa Rica, Cyprus, Czechoslovakia, Denmark,
Ecuador, Egypt, Finland, France, Federal Republic of
Germany, Ghana, Greece, Hong Kong, Iceland, India,
Indonesia, Ireland, Israel, Italy, Ivory Coast, Japan,
Jordan, South Korea, Kuwait, Lebanon, Malaysia,
Mauritius, Mexico, The Netherlands, New Zealand,
Nigeria, Norway, Oman, Pakistan, Panama, Peru,
Philippines, Poland, Portugal, Qatar, Saudi Arabia,
Senegal, Singapore, Republic of South Africa, Spain,
Sri Lanka, Sweden, Switzerland, Syria, Taiwan,
Thailand, Tunisia, Turkey, United Arab Emirates,
United Kingdom, Uruguay, U.S.S.R., Venezuela,
Yugoslavia, Zimbabwe.

Copyright ©1990, Tektronix, Inc. All rights reserved.
Printed in U.S.A. Tektronix products are covered by
U.S. and foreign patents, issued and pending.
Information in this publication supersedes that in all
previously published material. Specification and
price change privileges reserved. TEKTRONIX,
TEK, PLOT 10, TEKTEST, SCOPE-MOBILE,
and  are registered trademarks. For further
information, contact Tektronix, Inc., P.O. Box 500,
Beaverton, OR 97077. Phone: (503) 627-7111;
TWX: (910) 467-8708; TLX: 151754. Subsidiaries
and distributors worldwide.

Tektronix
COMMITTED TO EXCELLENCE